HONDA

CBR1000RR-R & RR-R SP 2020-2024

FITTING INSTRUCTIONS TO BE FITTED BY A QUALIFIED TECHNICIAN



THIS SHEET INCLUDES FITTING INSTRUCTIONS FOR THE FOLLOWING PARTS:

Secondary Alternator Cover Part No. EC-CBR1000RR-2020-1-GBR / Secondary Clutch Cover Part No. EC-CBR1000RR-2020-2-GBR / Secondary Pulse Cover Part No. EC-CBR1000RR-2020-3-GBR / Brake Lever Guard Part No. BLG-CBR1000-2004-GBR / Clutch Lever Guard Part No. CLG-CBR1000-2004-GBR / Paddock Stand Bobbin Set Part No. BA12-8-GBR-SET / Bullet Frame Sliders Part No. FS-CBR1000RR-2020-R / Lower Chain Guard Part No. CGA09-GBR

SECONDARY ALTERNATOR COVER PART NO. EC-CBR1000RR-2020-1-GBR

- 1. Remove original fairing panel.
- Remove 4 existing bolts from the stock Alternator cover, shown as position Bolt 1, 2, 3 & 4.
- Place the Secondary Alternator Cover over the stock cover.
- Assemble 4 replacement bolts (M6X35HHF) loosely in the correct position as shown.
- Tighten bolts to a Torque of 10Nm as per Manufacturer's recommendations.
 DO NOT OVERTIGHTEN.
- Replace fairing.



SECONDARY CLUTCH COVER PART NO. EC-CBR1000RR-2020-2-GBR

- Remove 3 existing bolts from the stock Clutch cover, shown as position Bolt 1, 2 & 3.
- 2. Place the Secondary Clutch Cover over the stock cover.
- Assemble the 3 replacement bolts loosely in the correct position as shown.
- Tighten bolts to a Torque of 10Nm as per Manufacturer's recommendations.
 DO NOT OVERTIGHTEN.





SECONDARY PULSE COVER PART NO. EC-CBR1000RR-2020-3-GBR

- 1. Remove 3 existing bolts from the stock Pulse cover, shown as position Bolt 1, 2 & 3.
- Place the Secondary Pulse Cover over the OEM stock cover.
- Assemble the 3 replacement bolts loosely in the correct position as shown.
- Tighten bolts to a Torque of 10Nm as per Manufacturer's recommendations.





HONDA CBR1000RR-R & RR-R SP 2020-2024

FITTING INSTRUCTIONS TO BE FITTED BY A QUALIFIED TECHNICIAN



BULLET FRAME SLIDER - LEFT HAND SIDE - RACE PART NO. FS-CBR1000RR-2020-LHS-R

Note: Fairing Requires No Modification

- 1. Remove lower engine / frame mounting bolt.
- 2. Assemble bolt through the aluminium bush into correct position.
- 3. Tighten to 64NM torque.
- 4. Slide bullet moulding onto aluminium bush.
- 5. Screw M6 bolt into front of bullet moulding hand tight.

PLEASE NOTE: These are only sold separately and are not available in our Bundles.





M12x1.25x50

BULLET FRAME SLIDER - RIGHT HAND SIDE - RACE PART NO. FS-CBR1000RR-2020-RHS-R

Note: Fairing Requires No Modification

- 1. Remove lower engine / frame mounting bolt.
- 2. Assemble bolt through the aluminium bush into correct position.
- 3. Tighten to 64NM torque.
- 4. Slide bullet moulding onto aluminium bush.
- 5. Screw M6 bolt into front of bullet moulding hand tight.

PLEASE NOTE: These are only sold separately and are not available in our Bundles.



CPM-3 CPB -12-25-15

M12x1.25x55



PADDOCK STAND / BOBBIN SET - PART NO. BA12-8-GBR-SET

- 1 Assemble M8 x 40mm Bolt through the moulded bobbin.
- 2 Tighten bolts to swing arm boss, 8 Nm. DO NOT OVERTIGHTEN







1 x Moulded Paddock Stand / Bobbin

LOWER CHAIN GUARD PART NO. CGA09-GBR

- 1 Assemble 2 off M6 x 20mm bolts and washers through the moulded lower chain guard into the Black Anodised aluminium mounting block CGA09-2.
- 2 Position the assembly underneath the swing arm, closing the gap to the rear sprocket.
 Note: There should be a 5mm minimum gap from the bike chain to the lower chain quard.
- 3 Mark the position of the Black Anodised block, relative to the swing arm.
- 4 Disassemble the assembly, leaving the block to be replaced into the correct position. Mark the C/Sunk fixing hole positions on the underside of the swing arm.
- 5 Drill & Tap the marked holes , M6 (Drill 5mm Dia. for tapping)
- 6 Re-assemble the lower chain guard to the fixed block.



