


FITTING INSTRUCTIONS

TO BE FITTED BY A QUALIFIED TECHNICIAN

Bullet Frame Slider: Left hand side - **RACE** Part No. **FS-R9-2025-LHS-R**

The left hand frame slider sits behind the fairing.


- 1 Remove left hand fairing.
- 2 Remove upper engine mounting bolt.
- 3 Assemble bolt through the aluminium bush into correct position.
- 4 Tighten to 45NM torque.
- 5 Slide bullet moulding onto aluminium bush.
- 6 Screw M6 bolt through moulding hand tight.
- 7 Refit fairing.



Bullet Frame Slider: Right hand side - **RACE** Part No. **FS-R9-2025-RHS-R**

You need to cut your race fairing.

- 1 Remove right hand fairing.
- 2 Remove upper engine mounting bolt.
- 3 Assemble bolt through the aluminium bush into correct position.
- 4 Tighten to 45NM torque.
- 5 Slide bullet moulding onto aluminium bush.
- 6 Screw M6 bolt through moulding hand tight.
- 7 Cut appropriate size hole in fairing as pictured.
- 8 Refit fairing.



SET: **Bullet Frame Slider Set: FS-R9-2025-R**

- Bullet Frame Slider: Left hand side - RACE Part No. FS-R9-2025-LHS-R
- Bullet Frame Slider: Right hand side - RACE Part No. FS-R9-2025-RHS-R

Replacement Bullet Moulded Part Part No. **CPM-3**

