Kawasaki 2800/E 2013-2016

FITTING INSTRUCTIONS TO BE FITTED BY A QUALIFIED TECHNICIAN



THIS SHEET INCLUDES FITTING INSTRUCTIONS FOR THE FOLLOWING PARTS:

Secondary Alternator Cover Part No. EC-Z800-2013-1-GBR / Secondary Clutch Cover Part No. EC-Z800-2013-2-GBR / Secondary Pulse Cover Part No. EC-Z800-2013-3-GBR

SECONDARY ALTERNATOR COVER PART NO. EC-Z800-2013-1-GBR

For Stock Fairings

- 1 Remove 4 existing bolts from the stock Alternator cover, shown as position Bolt 1, 2, 3 & 4.
- 2 Place the Secondary Alternator Cover over the stock cover.
- 3 Assemble 4 replacement bolts loosely in the correct position as shown.
- 4 Tighten bolts to a Torque of 11Nm as per Manufacturer's recommendations. DO NOT OVERTIGHTEN.





SECONDARY CLUTCH COVER PART NO. EC-Z800-2013-2-GBR

For Stock Fairings

- 1 Remove 4 existing bolts from the Stock Clutch cover, shown as position Bolt 1, 2, 3 & 4.
- 2 Place the Secondary Clutch Cover over the stock cover.
- 3 Assemble 4 replacement bolts loosely in the correct position as shown.
- 4 Tighten bolts to a Torque of 11Nm as per Manufacturer's recommendations.
 DO NOT OVERTIGHTEN.






SECONDARY CLUTCH COVER PART NO. EC-Z800-2013-3-GBR

For Stock Fairings

- 1 Remove 4 existing bolts from the Stock Pulse cover, shown as position Bolt 1, 2, 3 & 4.
- 2 Place the Secondary Pulse Cover over the stock cover. Take care to ensure that the cable guide bracket remains in place when securing the bolt at Bolt position 1.
- 3 Assemble 4 replacement bolts loosely in the correct position as shown.
- 4 Tighten bolts to a Torque of 11Nm as per Manufacturer's recommendations. DO NOT OVERTIGHTEN.





www.GBRacing.eu

Engine Cover Set: EC-Z800-2013-SET-GBR